



OAK PANELS WITH FINGERJOINT



READY TO USE PANELS

STANDARD SIZES IN STOCK,
SUPERIOR QUALITY, SANDED THICKNESS

18 mm	1m10 x 4m50	36 pcs/bundle
22 mm	1m10 x 4m50	30 pcs/bundle
30 mm	0m71 x 3m65	32 pcs/bundle
	0m81 x 3m65	32 pcs/bundle
	1m21 x 3m65	20 pcs/bundle
33 mm	1m10 x 4m50	20 pcs/bundle
40 mm	0m65 x 4m50	25 pcs/bundle
	0m65 x 5m10	25 pcs/bundle
	1m10 x 4m50	17 pcs/bundle
44 mm	1m10 x 4m50	15 pcs/bundle
51 mm	0m65 x 4m50	22 pcs/bundle
56 mm	0m65 x 4m50	20 pcs/bundle
63 mm	0m65 x 4m50	17 pcs/bundle
70 mm	0m65 x 4m50	15 pcs/bundle

SQUARES IN STOCK

70 x 70 x 4500	56 pcs/bundle
85 x 85 x 4500	55 pcs/bundle

Characteristics of the PANELS
kiln-dried 10 % (+/- 2 %), D4 glue,
lamellas approx 45 mm (38-52), uniform in each panel,
both sides sanded G150,
all panels individually plastic wrapped.

WE ALSO PRODUCE TO YOUR SPECIFICATIONS
panels, squares, door frames, glued table legs, etc.
minimum quantity: 5-10 m³
delivery time = approx 12 weeks.



With more than 5000 m³ permanent stock in panels
and 17 years of panel experience, DB Hardwoods
can guarantee a short delivery time (max 1 week)
and a consistent quality.

V.16.1



DB HARDWOODS
HIGH QUALITY HARDWOODS & SOLID PANELS

www.dbhardwoods.com





STANDARD SIZES IN STOCK, SANDED THICKNESS

18 mm	1100 x from 900 to 1200
	1100 x from 1300 to 1500
	1100 x from 1600 to 1900
	1100 x from 2000 to 2400
	1100 x from 2500 to 3100
22 mm	1100 x from 900 to 1200
	1100 x from 1300 to 1500
	1100 x from 1600 to 1900
	1100 x from 2000 to 2400
	1100 x from 2500 to 3000
33 mm	1100 x from 900 to 1200
	1100 x from 1300 to 1500
	1100 x from 1600 to 1900
	1100 x from 2000 to 2400
	1100 x from 2500 to 2900
40 mm	1100 x from 3000 to 3900
	1100 x from 900 to 1200
	1100 x from 1300 to 1500
	1100 x from 1600 to 1900
	1100 x from 2000 to 2400
42,5 mm	1100 x from 2500 to 2900
	1100 x from 3000 to 3900
44 mm	1100 x from 900 to 1200
	1100 x from 1300 to 1500
42,5 mm	650 x from 900 to 1200
44 mm	1100 x from 900 to 900

Length increases per 100 mm.

Characteristics of the PANELS

kiln-dried 10 % (+/- 2 %),
wide lamellas : average 80 mm/+,
D4 glue, both sides sanded G150,

