



# OAK PANELS WITH FINGERJOINT



READY TO USE PANELS

STANDARD SIZES IN STOCK,  
SUPERIOR QUALITY, SANDED THICKNESS

18 mm	1m10 x 4m50	36 pcs/bundle
22 mm	1m10 x 4m50	30 pcs/bundle
30 mm	0m71 x 3m65	32 pcs/bundle
	0m81 x 3m65	32 pcs/bundle
	1m21 x 3m65	20 pcs/bundle
33 mm	1m10 x 4m50	20 pcs/bundle
40 mm	0m65 x 4m50	25 pcs/bundle
	0m65 x 5m10	25 pcs/bundle
	1m10 x 4m50	17 pcs/bundle
44 mm	1m10 x 4m50	15 pcs/bundle
56 mm	0m65 x 4m50	20 pcs/bundle
63 mm	0m65 x 4m50	17 pcs/bundle
72 mm	0m65 x 4m50	15 pcs/bundle

SQUARES IN STOCK

70 x 70 x 4500	56 pcs/bundle
85 x 85 x 4500	55 pcs/bundle

Characteristics of the PANELS  
kiln-dried 10 % (+/- 2 %), D4 glue,  
lamellas approx 45 mm (38-52), uniform in each panel,  
both sides sanded G180,  
all panels individually plastic wrapped.

**WE ALSO PRODUCE TO YOUR SPECIFICATIONS**  
panels, squares, door frames, glued table legs, etc.  
minimum quantity: 5-10 m3  
delivery time = approx 12 weeks.



With more than 5000 m3 permanent stock in panels  
and 17 years of panel experience, DB Hardwoods  
can guarantee a short delivery time (max 1 week)  
and a constant quality.

V.18.1



**DB HARDWOODS**  
HIGH QUALITY HARDWOODS & SOLID PANELS

[www.dbhardwoods.com](http://www.dbhardwoods.com)

# OAK PANELS WITHOUT FINGERJOINT



READY TO USE PANELS



## STANDARD SIZES IN STOCK, SANFROMD THICKNESS

18 mm      1100 x from 900 to 1200  
                  1100 x from 1300 to 1500  
                  1100 x from 1600 to 1900  
                  1100 x from 2000 to 2400  
                  1100 x from 2500 to 3100

22 mm      1100 x from 900 to 1200  
                  1100 x from 1300 to 1500  
                  1100 x from 1600 to 1900  
                  1100 x from 2000 to 2400  
                  1100 x from 2500 to 2900

33 mm      1100 x from 900 to 1200  
                  1100 x from 1300 to 1500  
                  1100 x from 1600 to 1900  
                  1100 x from 2000 to 2400  
                  1100 x from 2500 to 2900  
                  1100 x from 3000

40 mm      1100 x from 900 to 1200  
                  1100 x from 1300 to 1500  
                  1100 x from 1600 to 1900  
                  1100 x from 2000 to 2400  
                  1100 x from 2500 to 2900  
                  1100 x from 3000

42,5 mm    650 x from 900 to 1200  
 70 x 70 x 740

## Characteristics of the PANELS

kiln-dried 10 % (+/- 2 %),  
 wide lamellas : average 80 mm/+,  
 D4 glue, both sides sanded G150,  
 all panels individually plastic wrapped.

